

Twist-to-Release Units



Ordering Guide: Twist-to-Release Units

Example:

Selection	1	2	3	4	5	6	7
Catalog Number	52	P	R	8	E	R	A

Use the selection information below to build your twist-to-release unit catalog number. Please contact your Siemens account manager for further ordering details.

52PR8ERA

- Twist-to-Release Pushbutton, 30mm
- Chrome
- 2-Pos, Maintained
- Red, Illuminated
- 1 3/4" Plastic
- Full Voltage, 120V
- Single LED
- 1NO-1NC

52BR8HRA

- Twist-to-Release Pushbutton, 30 mm
- BlackMax
- 2-Pos, Maintained
- Red, Illuminated
- 1 3/4" Plastic
- Transformer, 240V
- 1NO-1NC

Selection (1)

Class
52 30mm
(Oil Tight Products)

(2)

Finish
P Chrome
B BlackMax - Nema 4X

(3)

Product Type
R Push / Twist Release

(4)

Style
8 Plastic Head

Selection (5)

Operation
Full voltage ☀
B 6 - 8V AC/DC
C 12 - 13V AC/DC
D 24 - 28V AC/DC
E 120V AC/DC

Transformer ☀
G 120V AC
H 240V AC
J 480V AC
K 600V AC

LED module ☀
L 24V AC/DC
M 120V AC
N 240V AC

Lighting Placeholder ☀
X No lighting module¹
Non-Illuminated ☀
W No lighting module, non-illuminated

(6)

Color²
R Red ☀
2 Red ☀
S Green ☀
3 Green ☀
T Amber ☀
9 Yellow ☀
Z Less Operating Head ☀☀

(7)

Optional: LED and/or Contact Blocks
A 1 NO - 1 NC (1-52BJK)
AB 1 NO - 1 NC (1-52BJK) and LED Single Bulb³
XB LED Single Bulb³

Default is incandescent bulb.

Additional contact block arrangements are available upon request. See contact block table on page 32 for a complete list of contact block offerings.

- ☀ Illuminated
- ☀ Non-Illuminated

¹ Lighting module accessory kits can be ordered on page 31. When using LED, lens and LED bulb must match.

² Illuminated and non-Illuminated features cannot be mixed. Example: If full voltage (illuminated) has been selected, a color with an illuminated symbol must be used.

³ This option cannot be selected when using 12-13V Full Voltage or LED Module. All LED Modules utilize a single LED bulb. When selecting this in combination with 120V Full Voltage, only AC voltage can be used.