

Non-Illuminated Selector Switches



Ordering Guide: Non-Illuminated Selector Switches

Example:

52SW2AAB

- Selector Switch, 30mm
- BlackMax, Long Lever
- 2-Pos, Maintained
- White Insert
- CAM A

52SA2AABA1

- Selector Switch, 30mm
- Chrome, Short Lever
- 2-Pos, Maintained
- White Insert
- CAM A
- 1NO-1NC

Selection	1	2	3	4	5	6	7	8
Catalog Number	52	S	W	2	A	A	B	

Use the selection information below to build your non-illuminated selector switch catalog number. Please contact your Siemens account manager for further ordering details.

Selection (1)

Class

52 Pushbutton
(Oil Tight)

(2)

Product Type

S Selector Switch

(3)

Model

A Chrome, short lever
 B Chrome, long lever
 X BlackMax - NEMA 4X short lever
 W BlackMax - NEMA 4X long lever

(4)

Style

2 Non-Illuminated

(5)

CAM

A 2 Pos: CAM A
 B 3 Pos: CAM B
 C 3 Pos: CAM C
 D 3 Pos: CAM D
 E 3 Pos: CAM E
 G 3 Pos: CAM G
 H 4 Pos: CAM H

Please see page 34 for CAM selection.

Selection (6)

Description

2 Position

A Maintained all positions
 C Spring return from left

3 Position

A Maintained all positions
 B Spring Return from left
 C Spring Return from right
 D Spring Return from left & right

4 Position

A Maintained all positions

(7)

Color

2 Red
 3 Green
 4 Yellow
 B White
 N No lens/head

(8)

Optional: Contact Blocks and Mounting Positions

A0 1 NO - 1 NC (1-52BJK) Mounted on left
 A1 1 NO - 1 NC (1-52BJK) Mounted on right
 A2 2 NO - 2 NC (2-52BJK) Mounted one left and one right
 J0 1 NC (1-52BAJ) Mounted on left
 J1 1 NC (1-52BAJ) Mounted on right
 J2 2 NC (2-52BAJ) Mounted one left & one right
 J2K1 2NC - 1 NO (2-52BAJ & 1-52BAK) Mounted one left (52BAJ) & one right (52BAK)
 K0 1 NO (1-52BAK) Mounted on left
 K1 1 NC (1-52BAK) Mounted on right
 K2 2 NC (2-52BAK) Mounted one left and one right

Additional contact block combination arrangements are available upon request. See contact block table on page 32 for a complete list of contact block offerings.

See table at top of page 34 for contact block position.