

Push-to-Test / Illuminated Pushbuttons



Ordering Guide : Push-to-Test Units

Example:

52PT6G3A

- Push-to-Test Illum PB, 30mm
- Chrome
- Momentary
- Green, Illuminated
- Plastic Lens
- Transformer, 120V
- Incandescent Bulb
- 1NO-1NC

52BT6D3AB

- Push-to-Test Illum PB, 30mm
- BlackMax
- Momentary
- Green, Illuminated
- Plastic Lens
- Full Voltage, 24V
- Single LED
- 1NO-1NC

Selection	1	2	3	4	5	6	7
Catalog Number	52	P	T	6	G	3	A

Use the selection information below to build your push-to-test unit catalog number. Please contact your Siemens account manager for further ordering details.

Selection (1)

Class

52 30mm
(Oil Tight Products)

(2)

Finish

P Chrome
B BlackMax -
NEMA 4X

(3)

Product Type

T Push-to-test / Illuminated
Pushbutton

(4)

Style

6 Plastic Lens

Selection (5)

Operation

Full voltage
B 6 - 8V AC/DC
C 12 - 13V AC/DC
D 24 - 28V AC/DC
E 120V AC/DC

Transformer

G 120V AC
H 240V AC
J 480V AC
K 600V AC

LED Module

L 24V AC/DC
M 120V AC
N 240V AC

Lighting Placeholder

X No lighting module¹

(6)

Color

2 Red
3 Green
5 Blue
9 Amber
A Clear
B White
N No lens

(7)

Optional: LED, Contact Blocks and/or Guards

A 1 NO - 1 NC (1-52BJK)
AB 1 NO - 1 NC (1-52BJK)
and LED Single Bulb²
AV 1 NO - 1 NC (1-52BJK)
and Guarded
XB LED Single Bulb²
XV Guarded

Default is incandescent bulb.

Additional contact block arrangements are available upon request. See contact block table on page 32 for a complete list of contact block offerings.

¹ Lighting module accessory kits can be ordered on page 31. When using LED, lens and LED bulb must match.

² This option cannot be selected when using 12-13V Full Voltage or LED Module. All LED Modules utilize a single LED bulb. When selecting this in combination with 120V Full Voltage, only AC voltage can be used.